



	Xceed 1	Xceed 2	Xceed 3
Speech Understanding	OpenSound Navigator™	Level 1	Level 2
	- Balancing power effect	100%	50%
	- Max. noise removal	9 dB	5 dB
	OpenSound Optimizer™	•	•
	Noise Reduction LX	-	-
	Multiband Adaptive Directionality LX	-	-
	OpenSound Booster™	•	•
	Speech Guard™ LX	Level 1	Level 3
	Single compression LX	-	-
	Speech Rescue™ LX	•	•
Sound Quality	Clear Dynamics	•	-
	Spatial Noise Management	•	-
	Processing Channels	48	48
	Bass Boost (streaming)	•	•
Listening Comfort	Transient Noise Management	4 configurations	3 configurations
	Feedback shield LX	•	•
	Wind Noise Management	•	•
Personalization & Optimizing Fitting	YouMatic™ LX, NR levels	3 configurations	2 configurations
	Fitting Bands	14	12
	Multiple Directionality Options	•	•
	Adaptation Management	•	•
	Oticon Firmware Updater	•	•
	VC range and step size	•	•
Connecting to the World	Fitting Formulas	DSE, VAC+, NAL-NL1 + 2, DSL v5.0	DSE, NAL-NL1 + 2, DSL v5.0
	Stereo streaming (2.4 GHz)	•	•
	Oticon ON app	•	•
	ConnectClip	•	•
	Remote Control 3.0	•	•
	TV Adapter 3.0	•	•
	Phone Adapter 2.0	•	•
	Amigo FM	•	•
	Tinnitus SoundSupport™	•	•
	CROS/ BiCROS support	•	•
	Bimodal fitting panel	•	•

Oticon Xceed BTE SP is a super power hearing aid with a 13 size battery. It has separate push buttons for programs and volume for easy usage and control. It features T-coil, optional LED indications and FM support.

OpenSound Navigator™ helps power users to select and understand speech even in challenging sound environments by balancing the sound sources and suppressing background noise.

OpenSound Optimizer™ enhances both listening experience and comfort by blocking feedback and allowing the users to receive prescribed gain.

TwinLink™ wireless technology combines binaural communication and streaming, and 2.4 GHz connectivity for stereo streaming directly from digital sound sources.

Oticon Xceed is built on the Velox S™ platform using a programmable firmware architecture supporting future performance updates.

Conditions of Use

Operating conditions

Temperature: +34°F to +104°F

Humidity: 5% to 93% relative humidity, non-condensing

Atmospheric pressure: 700 hPa to 1060 hPa

Storage and transportation conditions

Temperature and humidity shall not exceed the below limits for extended periods during transportation and storage.








Temperature: -13°F to +140°F

Humidity: 5% to 93% relative humidity, non-condensing

Atmospheric pressure: 700 hPa to 1060 hPa


IP68

For information on compatibility, please visit www.oticon.com/support/compatibility. Apple, the Apple logo, iPhone®, iPad®, and iPod touch® are trademarks of Apple Inc., registered in the U.S. and other countries.

Technical data		Ear Simulator Measured according to IEC 60118-0:1983/AMD1:1994, IEC 60118-0:2015, IEC 60118-1:1995+AMD1:1998 CSV and IEC 60318-4:2010	2CC Coupler Measured according to ANSI S3.22-2014, IEC 60118-0:2015 and IEC 60318-5:2006
 110  DSE Fitting Range Hook, undamped Technical information Omnidirectional mode is used unless otherwise stated. Warning to the instrument dispenser The maximum output capability of the hearing aid may exceed 132 dB SPL. Special care should be exercised in selecting and fitting the instrument, as there may be risk of impairing the remaining hearing of the hearing aid user.		OSPL90  Full-on Gain  — Standard tube, undamped hook --- Standard tube, damped hook Frequency Response  — Acoustic input: 60 dB SPL --- Magnetic input: 31.6 mA/m	OSPL90  Full-on Gain  — Standard tube, undamped hook --- Standard tube, damped hook Frequency Response  — Acoustic input: 60 dB SPL --- Magnetic input: 31.6 mA/m
OSPL90	Peak 1600 Hz HFA-OSPL90	143 dB SPL 135 dB SPL 138 dB SPL	139 dB SPL 127 dB SPL 130 dB SPL
Full-on gain ¹	Peak 1600 Hz HFA-FOG	83 dB 75 dB 77 dB	79 dB 67 dB 70 dB
Reference test gain		61 dB	53 dB
Frequency range		100-6500 Hz	100-6100 Hz
Telecoil output (1600 Hz)	1 mA/m field 10 mA/m field SPLITS L/R	109 dB SPL 126 dB SPL -	- - 115 dB SPL
Total harmonic distortion (Input 70 dB SPL)	500 Hz 800 Hz 1600 Hz	4 % <2 % <2 %	4 % <2 % <2 %
Equivalent input noise level	Omni Dir	18 dB SPL 32 dB SPL	19 dB SPL 34 dB SPL
Battery consumption ²	Typical Quiescent	1.6 mA 1.4 mA	2.5 mA 1.4 mA
Battery life, artificial measurement, hours ³		200	125
Expected battery life, hours (battery size 13 - IEC PR48) ⁴		75-115	

- Measured with the gain control of the hearing aid set to its full-on position minus 20 dB and with an input SPL of 70 dB. This is to obtain a gain response equal to the full-on gain response from e.g. IEC 60118-0+A1:1994 but without influence of feedback.
- Battery current is measured according to IEC 60118-0:1983/AMD1:1994 §7.11, IEC 60118-0:2015 §7.7 and ANSI S3.22:2014 §6.13 after a settling time of minimum 3 minutes.
- Based on the standardized battery consumption measurement (IEC 60118-0:1983/AMD1:1994). The actual battery life depends on battery quality, use pattern, active feature set, hearing loss and sound environment.
- Real usage battery life is shown as an estimated interval based on mixed use cases with variable amplification settings and variable input levels, incl. direct stereo streaming from a TV (25% of the time) and streaming from a mobile phone (6% of the time).

 SBO Hearing A/S
Kongebakken 9
DK-2765 Smørum
Denmark
www.oticon.global

Headquarters:
Oticon A/S
Kongebakken 9
DK-2765 Smørum
Denmark
www.oticon.global