

TV-Streamer+





Technical data	
Dimensions	70.6 x 49.5 x 15.7 mm
Weight	32 g.
Power supply	USB compliant supply 5V DC
Power connection	USB-C
Power consumption	Max. 100 mA
Audio input	Analogue: Stereo 3.5 mm mini-jack --> L/R RCA Digital: Optical mini-TOSLINK connector
Supported digital audio formats	Stereo PCM at 32, 44.1 & 48 kHz sample rate AC3: 44.1 & 48 kHz sample rate
Line input sensitivity	16mV to 2V RMS entire range
Audio streaming	Multiple hearing instruments can stream from the TV-Streamer+
Wireless connections	Up to 8 TV-Streamer+ can be paired to a binaural set of hearing instruments
Streaming range	7 metres
Audio quality	Mono/Stereo 24 kHz sample rate Mono/Stereo 16 kHz sample rate (Auracast™ transmitter)
Audio bandwidth	Mono/Stereo 24 kHz sample rate: 75 Hz - 11 kHz +/-3 dB Mono/Stereo 16 kHz sample rate (Auracast transmitter): 75 Hz - 7 kHz +/-3 dB
Wireless frequency	2.4 GHz
Emission	Max. 12 dBm in compliance with all relevant standards
ESD tolerance	±8 kV contact ±15 kV air
Operating temperature	+5 °C to +40 °C
Storage & transportation temperature	-25 °C to +70 °C

4024180000GB-24.06-Rev.D

Worldwide Headquarters
GN Hearing A/S
Lautrupbjerg 7
DK-2750 Ballerup
Denmark
Tel.: +45 4575 1111
CVR no. 55082715

© 2023 GN Hearing A/S. All rights reserved.
The Auracast word mark and logos are trademarks owned by Bluetooth SIG, Inc.