Beltone **Rely**™




Super Power BTE

Model	RLY495-DW	RLY395-DW	RLY295-DW
Device Configurations			
Battery size		675 Zinc-Air	
IP Classification		IP 68	
Control option		Telecoil, DAI	
Audiological Features			
Curvilinear Rapid (WDRC)	12	8	6
Spatial Directionality	●		
Synchronised Speech Spotter Pro	●		
Speech Spotter Basic	●	●	●
Selectable Beamwidth	●	●	
Adaptive Directionality			●
Environmental Classifier	●	●	●
Feedback Eraser with WhistleStop	●	●	●
AFX Music Mode	●		
Sound Cleaner	●	●	●
Wind Noise Reduction	●	●	●
Impulse Noise Reduction	●		
Silencer	●	●	●
Synchronised Satisfy	●	●	
Tinnitus Breaker Pro	●	●	●
Functional Features			
Synchronised Push Button	●	●	
Synchronised Volume Control	●	●	
Delayed activation	●	●	●
Auto phone	●	●	●
Comfort Phone	●	●	
Direct audio streaming (MFi, Android™ *)	●	●	
Beltone Direct TV Link 2, myPAL Pro and Micro, Phone Link 2, Remote Control & Remote Control 2	●	●	●
Beltone HearMax™ app	●	●	●
Beltone Remote Care			
Remote Fine Tuning	●	●	●
Remote Care Live	●	●	●
Remote Firmware Updates	●	●	●
Fitting Features			
Fitting Software Beltone Solus Max™ 1.10 or higher	●	●	●
Fully Flexible Programs	4	4	4
Safeguard Feedback Control	●	●	●
Satisfaction Journal	●	●	●
Wireless Fitting with Noahlink Wireless	●	●	●

* Compatible with Android smartphones that support direct Android streaming to hearing aids

Fitting range



Made for iPhone | iPad | iPod

Works with android

© 2020 GN Hearing Care Corporation. All rights reserved. Beltone is a trademark of GN Hearing Care Corporation.
Apple, the Apple logo, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.
Android is a trademark of Google LLC.
The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.


Beltone™


Technical Specifications

		RLY95-DW		
		IEC 60118-0: 1983_AMD1:1994 IEC 60118-0:2015 (*) IEC 711 Ear Simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	62	53	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	86 74	83 67	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	144 136	141 130	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz 3200 Hz	4.7 0.8 0.8 -	4.2 0.5 0.7 0.2	%
Telecoil sensitivity (1 mA/m input) HFA - SPLIV @ 31.6 mA/m (ANSI) Full-on telecoil sensitivity @ 1mA/m	Max. HFA 1600 Hz/HFA	117 123 106	113 113 98	dB SPL
Equivalent input noise, w/o Noise reduction		23	27	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	7	8	dB SPL
Frequency range IEC 60118-0: 2015		100-6120*	100-5200	Hz
Current Drain (Quiescent / Operating)		1.3/1.7	1.3/3.3	mA
Weight of hering aid (without hook, tube and ear mould)		4.50 / 0.16		gram/oz


* Measured according to IEC60118-0:2015, with 711-Ear simulator coupler.


IEC 60118-0: 1983_AMD1:1994
IEC 711 Ear Simulator






ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler







Patents pending

All specifications are subject to change without notice

4014310000GB-2010-Rev.A

Worldwide Headquarters
Beltone A/S
Lautrupbjerg 7
DK-2750 Ballerup, Denmark
Tel.: +45 45 75 11 11
beltone.com

CVR no. 55082715

Australia
GN Hearing Australia Pty Ltd
Gate C, 19-25 Khartoum Road
Macquarie Technology Park
Macquarie Park NSW 2113
Tel.: (free) 1800 658 955
beltone.com/en-au

New Zealand
GN Hearing New Zealand Limited Ground
Floor, North Entrance
4 Fred Thomas Drive
Takapuna, Auckland, 0622
Tel.: (free) 0800 900 126
beltone.com