Beltone **Amaze™**



Product Description

The Beltone Amaze In-the-Canal (ITC) model has four receiver power levels to select: Low (LP), Medium (MP), High (HP), and Ultra (UP).

The Beltone Amaze product platform offers an extended bandwidth of up to 9.5 kHz, a higher input dynamic range of up to 116 dB SPL, and a strong base of CrossLink Directionality 2, a functionality that closely monitors surroundings and automatically switches to the most natural speech focus settings. The result is a truly amazing and individual hearing experience in all situations with a clearer, fuller, and richer sound quality.

The 6th generation 2.4 GHz wireless functionality allows cloud connectivity with Beltone Remote Care, enabling the hearing aids to communicate with each other. Direct audio streaming from iOS and Android™* devices is available for Beltone Amaze hearing aids. Telecoil is optionable for the ITC-DWT-models. Beltone Amaze ITC hearing aids are HPF80 NanoBlock-coated for optimum durability.

* Compatible from Android version 10 and Bluetooth® 5.0 with the Android streaming to hearing aids feature.

Model	AMZ17-ITC-DW AMZ17-ITC-DWT	AMZ9-ITC-DW AMZ9-ITC-DWT	AMZ6-ITC-DW AMZ6-ITC-DWT
Device Configurations			
Battery	312		
Power levels	*LP, MP, HP & UP		
Audiological Features			
Curvilinear Rapid (WDRC)	17	14	12
Spatial Directionality	●	●	●
Band-split Directionality	●	●	●
Adjustable Mixing point Frequency	●	●	
Speech Spotter Pro	●	●	
Speech Spotter Basic			●
Smart Beam Steering	●	●	
Adaptive Directionality	●	◉	○
Smart Gain Pro	●		
Smart Gain		●	
Sound Cleaner Pro	●	◉	
Sound Cleaner			●
Silencer	●	●	●
Impulse Noise Reduction	●	●	
Sound Shifter	●	●	●
Feedback Eraser with WhistleStop	●		
Feedback Eraser		◉	○
AFX Music Mode	●	●	●
Satisfy	●	●	●
Low Frequency Boost (Only UP)	●	●	○
Amplification Strategy (WDRC/Semi-Linear/Linear - Only UP)	●	●	◉
Tinnitus Breaker Pro	●	●	●
Functional Features			
Delayed Activation	●	●	●
Auto-Phone	●	●	●
Direct audio streaming	●	●	●
Beltone Direct TV Link 2, myPAL Pro and Micro, Phone Link 2, Remote Control & Remote Control 2	●	●	●
Beltone HearMax™ app	●	●	●
Beltone Remote Care			
Remote Fine Tuning	●	●	●
Remote Firmware Updates	●	●	●
Fitting Features			
Beltone Solus Max™ 1.6 or higher	●	●	●
Fully Flexible Programs	4	4	4
Safeguard Feedback Control	●	●	●
Satisfaction Journal	●	●	●
Noahlink Wireless	●	●	●


*LP is only available for AMZ17-ITC-DW, AMZ9-ITC-DW, AMZ6-ITC-DW.

○ Basic Settings


◉ Advanced Settings

● Ultimate Settings

Fitting Range - Closed



Fitting Range - Closed



Made for iPhone | iPad | iPod

© 2019 GN Hearing Care Corporation. All rights reserved. Beltone is a trademark of GN Hearing Care Corporation. Apple, the Apple logo, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google LLC. The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.

Beltone

401167000GB-19.12-Rev.C

Worldwide Headquarters
Beltone A/S
Lautrupbjerg 7
DK-2750 Ballerup,
Denmark
Tel.: +45 45 75 11 11
beltone.com

CVR no. 55082715

Australia
GN Hearing Australia Pty Ltd
Gate C, 19-25 Khartoum Road
Macquarie Technology Park
Macquarie Park NSW 2113
Tel.: (free) 1800 658 955
beltone.com/en-au

New Zealand
GN Hearing New Zealand Limited
Ground Floor, North Entrance
4 Fred Thomas Drive
Takapuna, Auckland, 0622
Tel.: (free) 0800 900 126
beltone.com

Beltone


Technical Specifications

		LP		MP		
		IEC 60118-0: 1983_AMD1:1994 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	IEC 60118-0: 1983_AMD1:1994 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	34	32	39	37	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	49 44	40 37	59 50	50 45	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	124 116	114 109	128 120	118 114	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz 3200 Hz	0.4 0.5 0.5 -	0.3 0.4 0.5 0.2	0.4 0.7 0.6 -	0.3 0.4 0.5 0.3	%
Telecoil sensitivity (1 mA/m input) *	Max.	-	-	90	79	dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	-	-	103	98	
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	-	-	82	76	
Equivalent input noise, w/o Noise reduction		22	22	25	23	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	11	10	10	10	
Frequency range IEC 60118-0: 2015		100-9570**	100-9150	100-9510**	100-8770	Hz
Current Drain (Quiescent / Operating)		1.19/1.21	1.19/1.31	1.17/1.19	1.17/1.31	mA


Data in accordance with IEC60118-0 Edition3.0 2015-06, IEC60118-7 and ANSI S3.22-2009, supply Voltage 1.3V


* Telecoil is only optionable for the ITC-DWT-models.
** Measured according to IEC60118-0:2015, with 711-Ear simulator coupler.


IEC 60118-0: 1983_AMD1:1994
IEC 711 Ear Simulator




ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler







LP
MP



Patents pending

All specifications are subject to change without notice


Technical Specifications

		HP		UP		
		IEC 60118-0: 1983_AMD1:1994 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	IEC 60118-0: 1983_AMD1:1994 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	47	42	60	47	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	69 58	60 53	78 70	70 62	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	130 126	120 119	137 137	129 124	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz 3200 Hz	0.8 1.9 0.8 -	0.5 0.8 0.6 0.2	0.4 1.0 0.2	0.4 0.5 0.1 0.1	%
Telecoil sensitivity (1 mA/m input) *	Max.	100	91	109	100	dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	111	103	119	109	
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	90	84	103	93	
Equivalent input noise, w/o Noise reduction		26	24	20	23	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	11	11	12	13	
Frequency range IEC 60118-0: 2015		100-7390**	100-6710	100-7390**	100-4810	Hz
Current Drain (Quiescent / Operating)		1.15/1.18	1.15/1.25	1.17/1.24	1.17/1.21	mA


Data in accordance with IEC60118-0 Edition3.0 2015-06, IEC60118-7 and ANSI S3.22-2009, supply Voltage 1.3V


* Telecoil is only optionable for the ITC-DWT-models.
** Measured according to IEC60118-0:2015, with 711-Ear simulator coupler.


IEC 60118-0: 1983_AMD1:1994
IEC 711 Ear Simulator




ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler







HP
UP



Patents pending

All specifications are subject to change without notice