Danavox Brisa

XF RIE



XF60S-DRWC XF61-DRW XF62-DRW

Model (Standard Receivers)	XF960S-DRWC XF961-DRW XF962-DRW	XF760S-DRWC XF761-DRW XF762-DRW	XF560S-DRWC XF561-DRW XF562-DRW	XF460S-DRWC XF461-DRW XF462-DRW
Device Configurations				
Battery size 60S-DRWC	Rechargeable Lithium-Ion			
Battery size 61-DRW	312 Zinc-Air			
Battery size 62-DRW	13 Zinc-Air			
Receiver Options	LP, MP, HP, UP			
Control Options	Tap control (60S-DRWC), Push button (61-DRW and 60S-DRWC), Multi-Function button (62), Telecoil (62)			
IP Classification	IP68			
Audiological Features				
Number of Channels	17	14	12	12
360 All-Around	●	–	–	–
All Access Directionality	–	●	–	–
Binaural Directionality III	–	–	●	–
Binaural Directionality	–	–	–	●
Spatial Sense	●	●	●	–
Front Focus	●	–	–	–
Ultra Focus	–	●	–	–
Synchronised Soft Switching	●	●	●	●
Environmental Optimiser II	●	–	–	–
Environmental Optimiser I	–	●	●	–
Noise Tracker II	5 settings	3 settings	2 settings	On/Off
Expansion	3 settings	2 settings	On/Off	On/Off
Impulse Noise Reduction	3 settings	3 settings	On/Off	On/Off
Wind Guard	3 settings	2 settings	On/Off	On/Off
Sound Shaper	●	●	●	●
DFS Ultra III (w/ Music Mode)	●	●	●	●
Synchronised Acceptance Manager	●	●	●	●
Tinnitus Sound Generator	●	●	●	●
Functional Features				
Ear-to-Ear Communication	●	●	●	●
Bluetooth® Auracast™	●	●	●	●
Direct audio streaming (compatible iOS* and Android™ devices)	●	●	●	●
TV-Streamer+	●	●	●	●
TV Streamer 2, Remote Control, Remote Control 2, Phone Clip+, Micro Mic and Multi Mic	●	●	●	●
BeMore app	●	●	●	●
Sound Enhancer (BeMore app)	●	–	–	–
Online Services				
Remote Fine Tuning	●	●	●	●
Live Assist	●	●	●	●
Remote Firmware Updates	●	●	●	●
Fitting Features				
Fitting Software XE BeMore 1.18 or higher	●	●	●	●
Fully Flexible Programs	4	4	4	4
Auto DFS	●	●	●	●
Datalogging	●	●	●	●
Wireless Fitting with Noahlink Wireless	●	●	●	●
Automatic Receiver Detection	●	●	●	●

* MFi supports hands-free calls for iPhone 11 or later, iPad Pro 12.9-inch (5th generation), iPad Pro 11-inch (3rd generation), iPad Air (4th generation), iPad mini (6th generation) or later, with software updates iOS 15.3 and iPadOS 15.3 or later.

Made for iPhone | iPad | iPod

Works with Android

DANAVOX GN

© 2023 GN Hearing A/S. All rights reserved. DANAVOX is a trademark of GN Hearing A/S. Apple, the Apple logo, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google LLC. The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The Auracast word mark and logos are trademarks owned by Bluetooth SIG, Inc.


4024630000GB-24.03-Rev.B



Desktop charger



Premium charger



Standard charger

Technical data	Premium charger	Standard charger	Desktop charger
Dimensions	99.4 x 35 x 67.5 mm / 3.9 x 1.4 x 2.7”	100.2 x 42 x 54.8 mm / 3.9 x 1.7 x 2.2”	82 x 36 x 46 mm / 3.2 x 1.4 x 1.8”
Weight	145 grams / 5.1 oz	95 grams / 3.3 oz	82 grams / 2.9 oz
Power supply	USB power supply, 5 V	USB power supply, 5 V	USB power supply, 5 V
Charging form factor (CFF)	8	8	8
Internal power source	Rechargeable Lithium Ion battery	N/A	N/A
Charging time for internal lithium ion battery in charger	Max 3,5 hours, depending on initial state of the battery	N/A	N/A
Battery life (fully charged, not connected to mains power)	Min. 3 full charges of 2 hearing instruments, without hearing instruments: 12 months	N/A	N/A
Charging time for hearing instrument	< 35 °C (95F): 3 hours, depending on initial state of the battery	< 35 °C (95F): 3 hours, depending on initial state of the battery	< 35 °C (95F): 3 hours, depending on initial state of the battery
Wireless communication and charging frequencies	2.4 GHz and 135 kHz	2.4 GHz and 135 kHz	2.4 GHz and 135 kHz
ESD tolerance	According to IEC 61000-4-2 Electrostatic discharge immunity test standard	According to IEC 61000-4-2 Electrostatic discharge immunity test standard	According to IEC 61000-4-2 Electrostatic discharge immunity test standard
Operating temperature	+ 5 °C (41F) to + 35 °C (95F) at a relative humidity range of 15% to 90%, non-condensing	+ 5 °C (41F) to + 35 °C (95F) at a relative humidity range of 15% to 90%, non-condensing	+ 5 °C (41F) to + 35 °C (95F) at a relative humidity range of 15% to 90%, non-condensing
Storage temperature for charger	– 25 °C (-13F) to + 5 °C (41F), + 5 °C (41F) to + 35 °C (95F) at a relative humidity up to 90%, non-condensing, > 35 °C (95F) to 60 °C (140F) at a water vapour pressure up to 50 hPa	– 25 °C (-13F) to + 5 °C (41F), + 5 °C (41F) to + 35 °C (95F) at a relative humidity up to 90%, non-condensing, > 35 °C (95F) to 70 °C (158F) at a water vapour pressure up to 50 hPa	– 25 °C (-13F) to + 5 °C (41F), + 5 °C (41F) to + 35 °C (95F) at a relative humidity up to 90%, non-condensing, > 35 °C (95F) to 70 °C (158F) at a water vapour pressure up to 50 hPa

GN Hearing A/S
Lautrupbjerg 7
DK-2750 Ballerup
Denmark
Tel.: +45 4575 1111
resound.com

GN Hearing India Private Limited,
NMS TITANIUM
4th Floor, Office No 401-408,
Plot No. 74, Sector No.15,
CBD Belapur,
Navi Mumbai - 400614

DANAVOX GN


Technical Specifications

		LP		MP		
		IEC 60118-0: 1983_AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	IEC 60118-0: 1983_AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	41	32	45	37	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	65 57	54 48	70 61	59 53	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	125 117	114 109	127 122	116 113	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	0.8 1.5 1.1	0.6 0.8 0.8	1.1 1.6 1.0	0.9 1.0 0.8	%
Telecoil sensitivity (1 mA/m input)*	Max.	96	85	100	88	
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	101	92	106	97	dB SPL
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	86	78	92	83	
Equivalent input noise, w/o Noise reduction		24	22	23	21	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	9	9	10	10	dB SPL
Frequency range		<200 - >8000	<200 - >8000	<200 - >8000	<200 - >8000	Hz
Battery Lifetime (Battery type Rechargeable)**		30 (max) 24 (typ)	30 (max) 24 (typ)	30 (max) 24 (typ)	30 (max) 24 (typ)	Hours
Current Drain (Quiescent / Operating) (Model 61-DRW, 62-DRW)		0.85 / 1.15	0.85 / 1.15	0.81 / 0.91	0.81 / 1.04	mA

* Telecoil is only for the XFx62-DRW models.
** Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment. Maximum number includes no streaming; typical number includes several hours of streaming.


IEC 60118-0: 1983_AMD1:1994
IEC 711 Ear Simulator

Maximum Output (OSPL 90)




ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler

Maximum Output (OSPL 90)




LP
MP


Full-On and Reference Test Gain




Full-On and Reference Test Gain



Fitting range



Full-On Telecoil Response*
Input level 10 mA/m



Patents pending.

All specifications are subject to change without notice.


Technical Specifications

		HP		UP		
		IEC 60118-0: 1983_AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	IEC 60118-0: 1983_AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	48	40	60	46	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	73 67	63 59	80 79	73 65	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	129 124	120 117	137 137	130 123	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	0.7 1.2 0.8	0.4 0.5 0.5	0.5 0.4 0.1	0.3 0.4 0.1	%
Telecoil sensitivity (1 mA/m input)*	Max.	103	93	109	101	
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	107	99	113	106	dB SPL
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	97	89	109	94	
Equivalent input noise, w/o Noise reduction		20	19	17	23	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	10	10	10	10	dB SPL
Frequency range		<200 - 7390	<200 - 6090	<200 - 5300	<200 - 4850	Hz
Battery Lifetime (Battery type Rechargeable)**		30 (max) 24 (typ)	30 (max) 24 (typ)	30 (max) 24 (typ)	30 (max) 24 (typ)	Hours
Current Drain (Quiescent / Operating) (Model 61-DRW, 62-DRW)		0.84 / 0.88	0.84 / 1.04	0.82 / 1.02	0.82 / 1.04	mA

* Telecoil is only for the XFx62-DRW models.
** Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment. Maximum number includes no streaming; typical number includes several hours of streaming.


IEC 60118-0: 1983_AMD1:1994
IEC 711 Ear Simulator

Maximum Output (OSPL 90)




ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler

Maximum Output (OSPL 90)




HP
UP


Full-On and Reference Test Gain




Full-On and Reference Test Gain



Fitting range



Full-On Telecoil Response*
Input level 10 mA/m



Patents pending.

All specifications are subject to change without notice.