Danavox Boreal

XD Mini RIE



XD60-DRWC


Model (MM Receiver)	XD960-DRWC	XD760-DRWC	XD560-DRWC	XD460-DRWC
Device Configurations				
Battery size 60-DRWC	Rechargeable Lithium-Ion			
Receiver Options	MM			
Control Options	Push button (PB)			
IP Classification	IP68			
Audiological Features				
Number of Channels	17	14	12	12
360 All-Around	●	–	–	–
All Access Directionality	–	●	–	–
Binaural Directionality III	–	–	●	–
Binaural Directionality	–	–	–	●
M&RIE	●	●	●	●
Front Focus	●	–	–	–
Ultra Focus	–	●	–	–
Synchronised Soft Switching	●	●	●	●
Environmental Optimiser II	●	–	–	–
Environmental Optimiser I	–	●	●	–
Noise Tracker II	5 settings	3 settings	2 settings	On/Off
Expansion	3 settings	2 settings	On/Off	On/Off
Impulse Noise Reduction	3 settings	3 settings	On/Off	On/Off
Wind Guard	3 settings	2 settings	On/Off	On/Off
DFS Ultra III (w/ Music Mode)	●	●	●	●
Synchronised Acceptance Manager	●	●	●	●
Tinnitus Sound Generator	●	●	●	●
Functional Features				
Ear to Ear Communication	●	●	●	●
Direct audio streaming	●	●	●	●
TV Streamer 2, Remote Control, Remote Control 2, Phone Clip+, Micro Mic and Multi Mic	●	●	●	●
BeMore app	●	●	●	●
Sound Enhancer (BeMore app)	●	–	–	–
Online Services				
Remote Fine Tuning	●	●	●	●
Live Assist	●	●	●	●
Remote Firmware Updates	●	●	●	●
Fitting Features				
Fitting Software XE BeMore 1.16 or higher	●	●	●	●
Fully Flexible Programs	4	4	4	4
Datalogging	●	●	●	●
Wireless Fitting with Noahlink Wireless	●	●	●	●
Automatic Receiver Detection	●	●	●	●



Desktop charger



Premium charger



Standard charger

Technical data	Premium charger	Standard charger	Desktop charger
Dimensions	99.4 x 35 x 67.5 mm / 3.9 x 1.4 x 2.7”	100.2 x 42 x 54.8 mm / 3.9 x 1.7 x 2.2”	82 x 36 x 46 mm / 3.2 x 1.4 x 1.8”
Weight	145 grams / 5.1 oz	95 grams / 3.3 oz	82 grams / 2.9 oz
Power Supply	USB power supply, 5 V	USB power supply, 5 V	USB power supply, 5 V
Charging form factor (CFF)	6	6	6
Internal Power Source	Rechargeable Lithium Ion battery, 3.6 V, 2600 mAh	N/A	N/A
Charging time for internal lithium ion battery in Charger	Max 3,5 hours, depending on initial state of the battery	N/A	N/A
Battery life (fully charged, not connected to mains power)	Min. 3 full charges of 2 hearing instruments, Without hearing instruments: 12 months	N/A	N/A
Charging time for Hearing Instrument	< 40 °C (104F): 3 hours, depending on initial state of the battery	< 40 °C (104F): 3 hours, depending on initial state of the battery	< 40 °C (104F): 3 hours, depending on initial state of the battery
Wireless frequency between Hearing Instrument and Charger	2.4 GHz and 333 kHz	2.4 GHz and 333 kHz	2.4 GHz and 333 kHz
ESD tolerance	According to IEC 61000-4-2 Electrostatic discharge immunity test standard	According to IEC 61000-4-2 Electrostatic discharge immunity test standard	According to IEC 61000-4-2 Electrostatic discharge immunity test standard
Operating & Charging temperature	+ 5 °C (41F) to + 40 °C (104F) at a relative humidity range of 15% to 90%, non-condensing	+ 5 °C (41F) to + 40 °C (104F) at a relative humidity range of 15% to 90%, non-condensing	+ 5 °C (41F) to + 40 °C (104F) at a relative humidity range of 15% to 90%, non-condensing
Storage temperature for charger and Hearing Instrument	– 25 °C (-13F) to + 5 °C (41F), + 5 °C (41F) to + 35 °C (95F) at a relative humidity up to 90%, non-condensing, > 35 °C (95F) to 70 °C (158F) at a water vapour pressure up to 50 hPa	– 25 °C (-13F) to + 5 °C (41F), + 5 °C (41F) to + 35 °C (95F) at a relative humidity up to 90%, non-condensing, > 35 °C (95F) to 70 °C (158F) at a water vapour pressure up to 50 hPa	– 25 °C (-13F) to + 5 °C (41F), + 5 °C (41F) to + 35 °C (95F) at a relative humidity up to 90%, non-condensing, > 35 °C (95F) to 70 °C (158F) at a water vapour pressure up to 50 hPa

Made for iPhone | iPad | iPod

Works with android

DANAVOX GN

© 2023 GN Hearing A/S. All rights reserved. DANAVOX is a trademark of GN Hearing A/S. Apple, the Apple logo, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google LLC.

402367000GB-23.05-Rev.B

GN Hearing A/S
Lautrupbjerg 7
DK-2750 Ballerup
Denmark
Tel.: +45 4575 1111
danavox.com

CVR no. 55082715

GN Hearing India Private Limited,
NMS TITANIUM
4th Floor, Office No 401-408,
Plot No. 74, Sector No.15,
CBD Belapur,
Navi Mumbai - 400614


DANAVOX GN


Technical Specifications


		MM		
		IEC 60118-0: 1983_AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	41	33	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	63 53	53 47	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	124 117	115 110	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	0.3 1.4 0.8	0.1 0.9 0.4	%
Equivalent input noise, w/o Noise reduction		22	20	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	7	7	dB SPL
Frequency range IEC60118-0:2015*		100-9550	100-9100	Hz
Battery Lifetime (Battery type Rechargeable)**		30 (Max) 24 (Typ)	30 (Max) 24 (Typ)	Hours

* Measured according to IEC 60118-0:2015, with 711-Ear simulator coupler.
** Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.


IEC 60118-0: 1983_AMD1:1994
IEC 711 Ear Simulator








ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler





Patents pending.
All specifications are subject to change without notice.