Danavox Barani

XA CIC



CIC

Model	XA9-CIC	XA7-CIC	XA5-CIC
Device Configurations			
Battery size	10A		
Power levels	LP, MP & HP		
Colors available	6		
Audiological Features			
Number of channels	17	14	12
Environmental Optimizer II	●	–	–
Environmental Optimizer	–	●	●
Noise Tracker II	5 settings	3 settings	2 settings
Expansion	3 settings	2 settings	On/Off
Impulse Noise Reduction	3 settings	3 settings	On/Off
Extended Bandwidth	●	●	●
Sound Shaper	●	●	●
DFS Ultra III (w/ Music Mode)	●	●	●
Acceptance Manager	●	●	●
Tinnitus Sound Generator	●	●	●
Fitting Features			
Fitting Software XE BeMore 1.18 or higher	●	●	●
Fully Flexible Programs	4	4	4
Auto DFS	●	●	●
Datalogging	●	●	●

DANAVOX GN


© 2023 GN Hearing A/S. All rights reserved.

Technical Specifications


		LP		MP		HP		
		IEC 60118-0: 1983_AMD1:1994 IEC60118-0:2015* IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	IEC 60118-0: 1983_AMD1:1994 IEC60118-0:2015* IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	IEC 60118-0: 1983_AMD1:1994 IEC60118-0:2015* IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	HFA	36	31	43	37	49	41	dB
Full-on gain (50 dB SPL input)	Max. HFA	51 45	40 37	62 52	50 45	69 58	60 52	dB
Maximum output (90 dB SPL input)	Max. HFA	125 117	114 108	127 122	116 114	131 127	121 118	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz 3200 Hz	1.0 1.4 0.8	0.8 1.0 0.8 0.2	0.7 0.7 0.7	0.6 0.5 0.4 0.3	0.9 0.8 0.2	0.5 0.7 0.2 0.2	%
Equivalent input noise, w/o Noise reduction		23	23	25	23	25	22	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	10	10	11	11	10	10	dB SPL
Frequency range		100 - >8000	100 - >8000	100 - >8000	100 - >8000	100 - 7690	100 - 7210	Hz
Current Drain (Quiescent / Operating) (Battery type 10)		0.51 / 0.53	0.53 / 0.73	0.52 / 0.57	0.52 / 0.87	0.54 / 0.60	0.54 / 0.75	mA

IEC 60118-0: 1983_AMD1:1994
IEC 711 Ear Simulator


Maximum Output (OSPL 90)



Full-On and Reference Test Gain




Fitting range




ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler

Maximum Output (OSPL 90)



Full-On and Reference Test Gain



LP
MP
HP

Patents pending

All specifications are subject to change without notice.

40254000GB-23.11-Rev.A

GN Hearing A/S
Lautrupbjerg 7
DK-2750 Ballerup
Denmark
Tel.: +45 4575 1111
danavox.com

CVR no. 55082715

GN Hearing India Private Limited,
NMS TITANIUM
4th Floor, Office No 401-408,
Plot No. 74, Sector No.15,
CBD Belapur,
Navi Mumbai - 400614

DANAVOX GN